

PRODUCT INFORMATION

COLOURPRINT CLASSIC Digital Print Material

DESCRIPTION: Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks. The material is very thin, but grants a high covering power. **Polyester** backing.

BASIC INFORMATION: Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:

TEMPERATURE: 165°C **TIME:** 15 Seconds **PRESSURE:** Medium

APPLICATION INSTRUCTIONS:

- 1) Print and cut the material.
- 2) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material.
- 3) Weed the exceeding material.
- 4) Remove the image from the backing using the **Siser Transparent Polyester T.T.D.** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes.
- 5) Heat apply
- 6) Remove application tape **hot**. Should you use other application tapes, follow the manufacturer's instructions.

SUITABLE FOR: Cotton, Polyester, Poly-Cotton Blends.
Not suitable for treated and dyed garments (sublimation inks).

WASHING: (Wait 24hrs after the heat transfer).

TEMPERATURE: 50°C Max - wash inside out - do not use bleach or other aggressive chemical agents.

DRY-CLEANING: No **TUMBLE DRY:** Not advisable.

N.B.: all information given in this sheet is based on our experience.

We recommend to always perform a test before starting standard production.

