

PRODUCT INFORMATION

COLOURPRINT NEW

Digital Print Material

DESCRIPTION: Very thin heat seal material, specifically formulated for ink jet solvent and eco solvent based inks.
Paper backing.

BASIC INFORMATION: Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:

TEMPERATURE: 160°-165°C

TIME: 15 Seconds

PRESSURE: Medium

APPLICATION INSTRUCTIONS:

- 1) Print and cut the material.
- 2) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material.
- 3) Weed the exceeding material.
- 4) Remove the image from the backing using the **Siser Transparent Polyester T.T.D.** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes.
- 5) Heat apply
- 6) Remove application tape **hot**. Should you use other application tapes, follow the manufacturer's instructions.

SUITABLE FOR: Cotton, Polyester, Poly-Cotton Blends.
Not suitable for treated and dyed garments (sublimation inks).

WASHING: (Wait 24hrs after the heat transfer).

TEMPERATURE: 50°C Max - wash inside out - do not use bleach or other aggressive chemical agents.

DRY-CLEANING: No

TUMBLE DRY: Not advisable.

N.B.: all information given in this sheet is based on our experience.

We recommend to always perform a test before starting standard production.



P.O. BOX 804, ALBURY, N.S.W. 2640 431 TOWNSEND ST., ALBURY, 2640 PHONE: (02) 6021 5900 FAX: (02) 6021 8081
EMAIL: sales@flexiprint.com.au WEB: www.flexiprint.com.au