

DIGITAL PRINT MATERIAL INFORMATION

COLOURPRINT PU MATT & GLOSS

DESCRIPTION: Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks.
Polyester backing, matt finish.

BASIC INFORMATION & APPLICATION INSTRUCTIONS: Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:

- 1) Set Machine Temperature at **165°C - 170°C**
- 2) Pre-Press Garment for 2-5 seconds to remove moisture.
- 3) **Remove Laminate Carrier in one even movement; not stopping.**
- 4) Place Colourprint PU Matt transfer in desired position.
- 5) Using **Firm Pressure**, heat apply for **20 seconds on Cotton & Poly Cotton. (16 seconds on Lycras & Nylons)**
- 6) Remove carrier film while **hot**.
- 7) Re-Press using a cover sheet such as Parchment Paper, Kraft Paper or Teflon for a further 2-3 seconds.

SUITABLE FOR: All types of Cotton, Polyester, Poly-Cotton Blends.
Not suitable for heavily dyed or dye sublimated materials especially Navy and Maroon.

WASHING: (Wait 24hrs after the heat transfer).

TEMPERATURE: 40°C Max - wash inside out - do not use bleach or other aggressive chemical agents.

DRY-CLEANING: No **TUMBLE DRY:** Not advisable.

N.B.: all information given in this sheet is based on our experience.

We recommend to always perform a test before starting standard production.

For more information on the range of Digital Print Materials we supply, please visit our website at:

www.flexiprint.com.au

