

DIGITAL PRINT MATERIAL INFORMATION

SUBLITHIN MATT™

DESCRIPTION: Heat seal material specifically formulated for ink jet solvent and eco based inks.

Application on dyed garments, (sublimation inks).

The special formulation and processing of the material creates a barrier to the dyes of the textile avoiding the sublimation bleed.

Polyester backing, matt finish.

BASIC INFORMATION & APPLICATION INSTRUCTIONS: Due to the many different base materials available on the market, the following heat transfer instructions are given as a guideline only:

- 1) Set Machine Temperature at **160°C - 165°C**
- 2) Pre-Press Garment for 2-4 seconds to remove moisture.
- 3) **Remove Laminate Carrier in one even movement; not stopping.**
- 4) Place Sublithin Matt transfer in desired position.
- 5) Using **Medium Pressure**, heat apply for **15 seconds**.
- 6) Remove carrier film while **hot**.
- 7) Re-Press using a cover sheet such as Parchment Paper, Kraft Paper or Teflon for a further 2-3 seconds.

SUITABLE FOR: Polyester fabrics dyed with sublimation inks

WASHING: (Wait 24hrs after the heat transfer).

TEMPERATURE: 30°C Max - wash inside out - do not use bleach or other aggressive chemical agents.

DRY-CLEANING: No **TUMBLE DRY:** Not advisable.

N.B.: all information given in this sheet is based on our experience.

We recommend to always perform a test before starting standard production.

For more information on the range of Digital Print Materials we supply, please visit our website at:

www.flexiprint.com.au

